

SPECIFICATIONS



TZS*06072

| | | | |
|--------------------------------|-------------------------|--------------------------------|-----------------------|
| Model No. | | TZSG06072 | TZSD06072J |
| Image Format Cover | | 1/3" ~ 1/4" | |
| Focal Length | | 6.0 ~ 72 mm | |
| Maximum Aperture Ratio | | 1 : 1.2 | |
| Zoom Ratio | | 12× | |
| Iris | Control Method | Video Drive | Direct Drive |
| | Iris Range | F1.2 ~ 360 | |
| | Speed | Approx. 2 sec | * * * |
| | Input Voltage & Current | DC 8 ~ 16V Max. 30mA | * * * |
| | Sensitivity Adjustment | 0.5 ~ 1.0VP-P | * * * |
| Focus | Control Method | Motorized/Preset | |
| | Speed | Approx. 2.5 sec | |
| | Input Voltage & Current | DC 12V Max. 50mA | |
| Zoom | Control Method | Motorized/Preset | |
| | Speed | Approx. 2 sec | |
| | Input Voltage & Current | DC 12V Max. 50mA | |
| Angle Field of View (D×H×V) | 1/4" | Wide | 41.0° × 32.9° × 24.7° |
| | | Tele | 3.7° × 3.0° × 2.2° |
| | 1/3" | Wide | 54.4° × 43.7° × 32.9° |
| | | Tele | 5.0° × 4.0° × 3.0° |
| Minimum Object Distance | | 1.5 m | |
| Back Focal Length | | 8.7 mm | |
| Effective Diameter | Front | φ 46.0 mm | |
| | Rear | φ 11.0 mm | |
| Filter Screw Size | | * * * | |
| Mount / Flange Back | | CS / 12.5mm | |
| Mechanical Dimension (W×H×L) | | 66mm × 82.5mm × 103.5mm | |
| Total Weight | | 570.0g | 570.0g |
| Application Temperature Range | | -10°C ~ +50°C (+14°F ~ +122°F) | |
| Comments | | | |

